

Safety Data Sheet

1. IDENTIFICATION



Product Name: Sealed Lead Acid Battery/ Optima Battery™ Synonyms: Sealed Lead Acid Battery	Product Use: Vehicle Electrical System Manufacturer/Supplier: Clarios Address: Florist Tower 5757 N. Green Bay Avenue Glendale, WI 53209-4408 US
General Information Number: (800)-333-2222 ext. 2267 Contact Person: Industrial Hygiene & Safety Department	Emergency number: CHEMTREC: 800-424-9300 <i>(For US & Canada use only)</i>

NOTE: The Clarios sealed cell/battery is considered an article as defined by 29 CFR 1910.1200 (OSHA Hazard Communication Standard). The information contained in this SDS is supplied at the customer's request for information only.

2. HAZARD(S) IDENTIFICATION

Health		Environmental		Physical
Acute Toxicity (Oral, dermal, inhalation)	Category 4	Aquatic	Chronic 1	
Skin corrosion/irritation	Category 1A	Aquatic	Acute 1	
Eye Damage	Category 1			
Reproductive	Category 1A			
Carcinogenicity (lead)	Category 1B			
Carcinogenicity (acid mist)	Category 1A			
Specific target organ toxicity (repeated exposure)	Category 2			

Label Elements:

Health	Environmental	Physical
		
Hazard Statements DANGER! Causes severe skin burns and eye damage. Causes serious eye damage. Harmful if swallowed, harmful if inhaled, harmful in contact with skin May damage fertility or the unborn child if ingested or inhaled. May cause cancer if ingested or inhaled. Causes damage to central nervous system, blood and kidneys through prolonged or repeated exposure.	Precautionary Statements Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing, eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Causes skin irritation, serious eye damage. Contact with internal components may cause irritation or severe burns. Avoid contact with internal acid. Irritating to eyes, respiratory system, and skin.	

May form explosive air/gas mixture during charging.

3. COMPOSITION / INFORMATION ON INGREDIENTS

INGREDIENTS (Chemical/Common Names):	CAS No.:	% by Wt:
Lead	7439-92-1	63 - 91
Sulfuric Acid	7664-93-9	17 - 25
Case Material Polypropylene	9010-79-1	2 - 6
Separator/Paster Paper Fibrous Glass	65997-17-3	<1 - 4

Composition Comments All concentrations are in percent by weight.

4. FIRST AID MEASURES

Note: Under normal conditions of battery use, internal components will not present a health hazard. The following information is provided for battery electrolyte (acid) and lead for exposures that may occur during battery production or container breakage or under extreme heat conditions such as fire.

Inhalation	Sulfuric Acid: Remove to fresh air immediately. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Consult a physician. Lead: Remove from exposure, gargle, wash nose and lips; consult physician.
Skin contact	Sulfuric Acid: Flush with large amounts of water for at least 15 minutes; remove contaminated clothing completely, including shoes. If symptoms persist, seek medical attention. Wash contaminated clothing before reuse. Discard contaminated shoes. Lead: Wash immediately with soap and water.
Eye contact	Sulfuric Acid and Lead: Flush immediately with large amounts of water for at least 15 minutes while lifting lids; Seek immediate medical attention if eyes have been exposed directly to acid.
Ingestion	Sulfuric Acid: Give large quantities of water; Do NOT induce vomiting or aspiration into the lungs may occur and can cause permanent injury or death; consult physician. Lead: Consult physician immediately.

5. FIRE FIGHTING MEASURES

Flash Point	Hydrogen – 259 °C
Auto ignition Temperature	Hydrogen – 580 °C
Flammable Limits	LEL = 4.1% (Hydrogen Gas in air) ; UEL = 74.2%
Extinguishing Media	CO ₂ ; foam; dry chemical. Do not use carbon dioxide directly on cells. Avoid breathing vapors. Use appropriate media for surrounding fire.
Special Fire Fighting Procedures	Use positive pressure, self-contained breathing apparatus. Beware of acid splatter during water application and wear acid-resistant clothing, gloves, face and eye protection. If batteries are on charge, shut off power to the charging equipment, but note that strings of series connected batteries may still pose risk of electric shock even when charging equipment is shut down.
Unusual Fire and Explosion Hazard	Highly flammable hydrogen gas is generated during charging and operation of batteries. If ignited by burning cigarette, naked flame or spark, may cause battery explosion with dispersion of casing fragments and corrosive liquid electrolyte. Carefully follow manufacturer's instructions for installation and service. Keep away all sources of gas ignition and do not allow metallic articles to simultaneously contact the negative and positive terminals of a battery. Follow manufacturer's instructions for installation and service.

6: ACCIDENTAL RELEASE MEASURES

Protective Measures to be	Stop flow of material, contain/absorb small spills with dry sand, earth, and vermiculite. Do not use combustible materials. If possible, carefully neutralize spilled electrolyte with soda ash, sodium bicarbonate, lime, etc. Wear acid-resistant clothing, boots, gloves, and face shield. Do not allow discharge
----------------------------------	--

Taken if Material is Released or Spilled	of un-neutralized acid to sewer. Acid must be managed in accordance with approved local, state, and federal requirements. Consult state environmental agency and/or federal EPA.
Waste Disposal Method	Dispose of as a hazardous waste. Dispose of in accordance with applicable local, state and federal regulations.

7. HANDLING AND STORAGE

Handling	Do not carry battery by terminals. Do not drop battery, puncture, or attempt to open battery case. Avoid contact with the internal components of a battery. Do not subject product to open flame or fire and avoid situations that could cause arcing between terminals.
Storage	Store batteries under roof in cool, dry, well-ventilated areas separated from incompatible materials and from activities that may create flames, spark, or heat. Store sealed lead acid batteries at ambient temperature.
Charging:	There is a possible risk of electric shock from charging equipment and from strings of series connected batteries, whether or not being charged. Shut-off power to chargers whenever not in use and before detachment of any circuit connections. Batteries being charged may generate and release flammable hydrogen gas. Charging space should be ventilated. Prohibit smoking and avoid creation of flames and sparks nearby. Wear face and eye protection when near batteries being charged.
Other	Follow Manufacturers Recommendations regarding maximum recommended currents and operating temperature range. Do not overcharge beyond the recommended upper charging voltage limit. Applying pressure or deforming the battery may lead to disassembly followed by eye, skin and throat irritation.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Occupational exposure limits

US OSHA Specifically Regulated Substances (29 CFR 1910.1001 – 1050)

Ingredient	CAS Number	Type	Value
Lead	7439-92-1	TWA	0.05 mg/m ³

US OSHA Table Z-1 Limits for Air Contaminants (29CFR 1910.1000)

Ingredient	CAS Number	Type	Value
Sulfuric Acid	7664-93-9	PEL	1 mg/m ³

US ACGIH Threshold Limit Values

Ingredient	CAS Number	Type	Value	Form
Lead	7439-92-1	TWA	0.05 mg/m ³	
Sulfuric Acid	7664-93-9	TWA	0.2 mg/m ³	Thoracic Fractions

US NIOSH: Pocket Guide to Chemical Hazards

Ingredient	CAS Number	Type	Value	Form
Sulfuric Acid	7664-93-9	TWA	1 mg/m ³	
Separator/Paster Paper Fibrous Glass	65997-17-3	TWA	3 fibers/cm ³ 5 mg/ m ³ 5 mg/ m ³	Fiber Fibers, total dust Fiber Total
Lead	7439-92-1	TWA	0.05 mg/m ³	

International Exposure Limits (mg/m³)

*Chemical & Common Name	Quebec PEV	Ontario OEL	EU OEL
Lead and Lead Compounds (inorganic)	0.05	0.05	0.15 (a)
Electrolyte (H ₂ SO ₄ /H ₂ O)	1	0.2	0.05 (b)

(a) As inhalable aerosol (b) Thoracic fraction

Biological limit values

ACGIH Biological Exposure Indices

Ingredient	Value	Determinant	Specimen	Sampling Time
Lead	300 µg/l	Lead	Blood	*

* - For Sampling details please see the source document.

Engineering Controls (Ventilation):

Store sealed lead acid batteries at ambient temperature. Never recharge batteries in an unventilated, enclosed space. Do not subject product to open flame or fire. Avoid conditions that could cause arcing between terminals.

Respiratory Protection (NIOSH/MSHA approved):

NONE REQUIRED FOR NORMAL HANDLING OF THE FINISHED PRODUCT.

When concentrations of sulfuric acid mist are known to exceed PEL, use NIOSH or MSHA-approved respiratory protection.

Skin Protection:

NONE REQUIRED FOR NORMAL HANDLING OF THE FINISHED PRODUCT.

If battery case is damaged, use rubber or plastic acid-resistant gloves with elbow-length gauntlet, acid-resistant apron, clothing and boots.

Eye Protection:

NONE REQUIRED FOR NORMAL HANDLING OF THE FINISHED PRODUCT.

If necessary to handle damaged product where exposure to the organic electrolyte is a possibility, chemical splash goggles and a face shield are recommended.

Other Protection:

Safety footwear meeting the requirements of ANSI Z 41.1 is recommended when it is necessary to handle the finished product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance and Odor	Manufactured article; no apparent odor. Electrolyte is a clear liquid with a sharp, penetrating, pungent odor.	
Odor Threshold	Not applicable.	
pH	Not applicable	
Boiling Point	Not applicable unless individual components exposed. Battery Electrolyte (Acid) - 230 - 233.6 °F (110 - 112 °C) Lead - 3191 °F (1755 °C)	
Melting Point	Lead - 621.32 °F (327.4 °C)	
Specific Gravity (H₂O = 1)	1.215 to 1.350	
Flash Point	498.2 °F (259.0 °C) Hydrogen	
Evaporation Rate (Butyl Acetate = 1)	< 1	
Vapor Pressure (mm Hg @ 20 ° C)	Battery Electrolyte (Acid) 11.7	
Flammability		
Upper/lower flammability or explosive limits	Hydrogen	Flammability Limit Lower- 4.1 % Flammability Limit Upper – 74.2 %
Vapor Pressure	Not applicable.	
Vapor Density	3.4 (Air = 1) Battery Electrolyte (Acid)	
Relative Density	1.21 - 1.3 Battery Electrolyte (Acid)	
Solubility	Lead and Lead dioxide are not soluble. 100 % Battery Electrolyte (Acid).	
% Volatile by Weight	Not applicable unless individual components exposed.	
Partition coefficient (n-octanol/water)	Not applicable	

Auto-ignition temperature	1076 °F (580 °C) Hydrogen.
Decomposition temperature	Not applicable
Viscosity	Not applicable

10. STABILITY AND REACTIVITY

Stability	The sealed battery is considered stable.
Conditions to Avoid	Sparks and other sources of ignition; high temperature; over charging.
Incompatibility (materials to avoid)	Electrolyte: Contact with combustibles and organic materials may cause fire and explosion. Also reacts violently with strong reducing agents, metals, sulfur trioxide gas, strong oxidizers, and water. Contact with metals may produce toxic sulfur dioxide fumes and may release flammable hydrogen gas.
Hazardous Decomposition Products	Lead compounds: Avoid contact with strong acids, bases, halides, halogenates, potassium nitrate, permanganate, peroxides, nascent hydrogen, and reducing agents. Electrolyte: Sulfur trioxide, carbon monoxide, sulfuric acid mist, sulfur dioxide, hydrogen sulfide.
Hazardous Polymerization	Lead compounds: Temperatures above the melting point are likely to produce toxic metal fume, vapor, or dust; contact with strong acid or base or presence of nascent hydrogen may generate highly toxic arsine gas. Will not occur.

11. TOXICOLOGICAL INFORMATION

NOTE: Under normal conditions of use, this product does not present a health hazard. The following information is provided for organic electrolyte and lead exposure that may occur due to container breakage or under extreme conditions such as fire. Organic electrolyte – reacts with moisture/water to produce hydrofluoric acid in trace quantities. Hydrofluoric acid is extremely corrosive and toxic. In severe exposures it acts as a systemic poison and causes severe burns. The reaction may be delayed. Any contact with this material, even minor, requires immediate medical attention.

ROUTES AND METHODS OF ENTRY

Inhalation	EXPOSURE IS NOT EXPECTED FOR PRODUCT UNDER NORMAL CONDITIONS OF USE. Sulfuric Acid: Breathing of sulfuric acid vapors or mists may cause severe respiratory irritation. Lead Compounds: Inhalation of lead dust or fumes may cause irritation of upper respiratory tract and lungs.
Skin Contact	EXPOSURE IS NOT EXPECTED FOR PRODUCT UNDER NORMAL CONDITIONS OF USE. Sulfuric Acid: Severe irritation, burns and ulceration. Lead Compounds: Not absorbed through the skin.
Skin Absorption	EXPOSURE IS NOT EXPECTED FOR PRODUCT UNDER NORMAL CONDITIONS OF USE. In the event of overcharging or damage to the unit, exposure to organic electrolyte solution/mist is possible. Extreme exposures to the organic electrolyte can be absorbed through the skin.
Eye Contact	EXPOSURE IS NOT EXPECTED FOR PRODUCT UNDER NORMAL CONDITIONS OF USE. Sulfuric Acid: Severe irritation, burns, cornea damage, and blindness. Lead Compounds: May cause eye irritation.
Ingestion	EXPOSURE IS NOT EXPECTED FOR PRODUCT UNDER NORMAL CONDITIONS OF USE. Sulfuric Acid: May cause severe irritation of mouth, throat, esophagus and stomach. Lead Compounds: Acute ingestion may cause abdominal pain, nausea, vomiting, diarrhea and severe cramping. This may lead rapidly to systemic toxicity and must be treated by a physician.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

Acute Effects	EXPOSURE IS NOT EXPECTED FOR PRODUCT UNDER NORMAL CONDITIONS OF USE. Sulfuric Acid: Severe skin irritation, damage to cornea, upper respiratory irritation. Lead Compounds: Symptoms of toxicity include headache, fatigue, abdominal pain, loss of appetite, muscular aches and weakness, sleep disturbances and irritability
---------------	---

Chronic Effects

EXPOSURE IS NOT EXPECTED FOR PRODUCT UNDER NORMAL CONDITIONS OF USE.

Sulfuric Acid: Possible erosion of tooth enamel, inflammation of nose, throat & bronchial tubes.
Lead Compounds: Anemia; neuropathy, particularly of the motor nerves, with wrist drop; kidney damage; reproductive changes in males and females. Repeated exposure to lead and lead compounds in the workplace may result in nervous system toxicity. Some toxicologists report abnormal conduction velocities in persons with blood lead levels of 50 µg/100 ml or higher. Heavy lead exposure may result in central nervous system damage, encephalopathy and damage to the blood-forming (hematopoietic) tissues.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

Overexposure to sulfuric acid mist may cause lung damage and aggravate pulmonary conditions. Contact of sulfuric acid with skin may aggravate diseases such as eczema and contact dermatitis. Lead and its compounds can aggravate some forms of kidney, liver and neurologic diseases.

ADDITIONAL HEALTH DATA

All heavy metals, including the hazardous ingredients in this product, are taken into the body primarily by inhalation and ingestion. Most inhalation problems can be avoided by adequate precautions such as ventilation and respiratory protection covered in Section 8. Follow good personal hygiene to avoid inhalation and ingestion: wash hands, face, neck and arms thoroughly before eating, smoking or leaving the work site. Keep contaminated clothing out of non-contaminated areas, or wear cover clothing when in such areas. Restrict the use and presence of food, tobacco and cosmetics to non-contaminated areas. Work clothes and work equipment used in contaminated areas must remain in designated areas and never taken home or laundered with personal non-contaminated clothing. This product is intended for industrial use only and should be isolated from children and their environment.

The 19th Amendment to EC Directive 67/548/EEC classified lead compounds, but not lead in metal form, as possibly toxic to reproduction. Risk phrase 61: May cause harm to the unborn child, applies to lead compounds, especially soluble forms.

Toxicological Data

Constituents	Species	Test Results
Sulfuric Acid (CAS 7664-93-9)		
Acute		
<i>Oral</i>		
LD50	Rat	2140 mg/kg

CARCINOGENICITY

Sulfuric Acid: The International Agency for Research on Cancer (IARC) has classified "strong inorganic acid mist containing sulfuric acid" as a Category I carcinogen, a substance that is carcinogenic to humans. This classification does not apply to liquid forms of sulfuric acid or sulfuric acid solutions contained within a battery. Inorganic acid mist (sulfuric acid mist) is not generated under normal use of this product. Misuse of the product, such as overcharging, may result in the generation of sulfuric acid mist.

Lead Compounds: Lead is listed as a 2B carcinogen, likely in animals at extreme doses. Proof of carcinogenicity in humans is lacking at present.

IARC Monographs. Overall Evaluation of Carcinogenicity

Lead (CAS 7439-92-1) 2B Possibly carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity	May damage fertility or the unborn child.
Specific target organ toxicity - single exposure	No data available.
Specific target organ toxicity - repeated exposure	Lead: May cause damage to organs (blood, central nervous system) through prolonged or repeated exposure.
Aspiration hazard	Not classified.

12. ECOLOGICAL INFORMATION

Environmental Fate	Lead is very persistent in soil and sediments. No data on environmental degradation. Mobility of metallic lead between ecological compartments is slow. Bioaccumulation of lead occurs in aquatic and terrestrial animals and plants but little bioaccumulation occurs through the food chain. Most studies include lead compounds and not elemental lead
Ecotoxicity	Very toxic to aquatic life with long lasting effects. However, no ecological impacts expected under normal use conditions.

Constituents	Species	Test Results
Inorganic Lead/Lead Compounds (CAS 7439-92-1)		
Aquatic Fish	LC50 Rainbow trout, Donaldson trout (Oncorhynchus mykiss)	1.17 mg/l, 96 hours
Persistence and Degradability	No data available	
Bioaccumulative potential	No data available	
Additional Information	No known effects on stratospheric ozone depletion Volatile organic compounds: 0% (by Volume) Water Endangering Class (WGC): NA	

13. DISPOSAL CONSIDERATIONS

Waste disposal method	Material should be recycled if possible. Lead-acid batteries are completely recyclable. Dispose waste and residues in accordance with applicable federal, state, and local regulations.
Hazardous waste code	D008: Lead
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or packaging may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. TRANSPORT INFORMATION

Note: Transportation requirements do not apply once the battery pack has been installed in a vehicle as part of the vehicle's functional components.

Transportation: Sealed Lead Acid / OPTIMA Battery is not a DOT Hazardous Material

Other: Per DOT, IATA, ICAO, and IMDG rules and regulations, these batteries are exempt from "UN2800" classification as a result of successful completion of the following tests:

- 1.) Vibration tests
- 2.) Pressure Differential Tests
- 3.) Case Rupturing Tests (no free liquids)

GROUND – US-DOT/CAN-TDG/EU-ADR/APEC-ADR:

Not regulated as dangerous goods per 49 CFR 173.159a

AIRCRAFT – ICAO-IATA:

Not regulated as dangerous goods per Special Provision A67

I VESSEL – IMO-IMDG:

Not regulated as dangerous goods per exception 238

15. REGULATORY INFORMATION

This product is an article pursuant to 29 CFR 1910.1200 and as such is not subjected to the OSHA Hazard Communication Standard. The information on this SDS is supplied at customer's request for information only.

TSCA

Ingredients listed in the TSCA registry are lead, lead compounds, and sulfuric acid.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Lead (CAS 7439-92-1)	Reproductive toxicity Central nervous system Kidney
----------------------	---

Blood
Acute toxicity

CERCLA Hazardous Substance List (40 CFR 302.4)

Lead (CAS 7439-92-1) LISTED
Sulfuric Acid (CAS 7664-93-9) LISTED

Superfund Amendment and Reauthorization Act of 1986 (SARA)

Hazard Categories
Immediate Hazard – Yes
Delayed Hazard – Yes
Fire Hazard – Yes
Pressure Hazard – Yes
Reactivity Hazard – Yes

SARA 302 Extremely hazardous substance

Chemical Name	CAS Number	Reportable Quantity	Threshold Planning Quantity	Threshold Planning Quantity – Lower value	Threshold Planning Quantity – upper value
Sulfuric Acid	7664-93-9	1000	1000 lbs.		

SARA 311/312 Hazard Categorization:

EPCRA Section 312 Tier Two reporting is required for non-automotive batteries if sulfuric acid is present in quantities of 500 lbs. or more and/or if lead is present in quantities of 10,000 lbs. or more. For more information consult 40 CFR 370.10 and 40 CFR 370.40

SARA 313 EPCRA Toxic Substances:

40 CFR section 372.38 (b) states: If a toxic chemical is present in an article at a covered facility, a person is not required to consider the quantity of the toxic chemical present in such article when determining whether an applicable threshold has been met under § 372.25, § 372.27, or § 372.28 or determining the amount of release to be reported under § 372.30. This exemption applies whether the person received the article from another person or the person produced the article. However, this exemption applies only to the quantity of the toxic chemical present in the article.

SARA 313 (TRI Reporting)

Chemical Name	CAS Number	% by weight
Lead	7439-92-1	63 - 91
Sulfuric Acid	7664-93-9	17 - 25

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Lead (CAS 7439-92-1)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Sulfuric Acid (CAS 7664-93-9)

Safe Drinking Water Act (SDWA)

Not regulated

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and

Chemical Code Number

Sulfuric acid (CAS 7664-93-9) 6552

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Sulfuric acid (CAS 7664-93-9) 20 % WV

DEA Exempt Chemical Mixtures Code Number

Sulfuric acid (CAS 7664-93-9) 6552

US State Regulations

US. Massachusetts RTK – Substance List

Lead (CAS 7439-92-1)

Sulfuric Acid (CAS 7664-93-9)

US New Jersey Worker and Community Right-to-know Act

Lead (CAS 7439-92-1)

Sulfuric acid (CAS 7664-93-9)

Separator/Paster Paper Fibrous Glass (CAS 65997-17-3)

US Pennsylvania Worker and Community Right-to-know Law

Lead (CAS 7439-92-1)

Sulfuric acid (CAS 7664-93-9)

US Rhode Island RTK

Lead (CAS 7439-92-1)
Sulfuric acid (CAS 7664-93-9)

US. California Proposition 65

WARNING: This product contains chemicals known to the State of California to cause cancer. Battery posts, terminals and related accessories contain lead and lead compounds, chemicals known to the state of California to cause cancer and reproductive harm. Wash hands after handling.

*Battery companies not party to the 1999 consent judgment with Mateel Environmental Justice Foundation should include a Proposition 65 Warning that complies with the current version of Proposition 65.

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Lead (CAS 7439-92-1)
Sulfuric acid (CAS 7664-93-9)


International Inventories

Country(s) or Region	Inventory Name	On inventory (yes/no)*
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

* A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. OTHER INFORMATION

Issue Date: 04/01/2015
Further information: NFPA Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3=Serious 4 = Severe
NFPA ratings



US Military National Stock Number (NSN)

Model Number	P/N	NSN
34/78	8004-003	6140-01-374-2243
34	8002-002	6140-01-378-8232
34R	8003-151	6140-01-475-9357
34VX	8008-158	6140-01-534-6466
25	8025-160	
35	8020-164	
75/25	8022-091	6140-01-475-9361
78	8078-109	
850/6 – 1050 SLI	8010-044	6140-01-475-9414
DS46B24R	8171-767	
850/6 – 950 (DC)		
D51	8071-167	6140-01-523-6288
D51R	8073-167	6140-01-529-7226
D35	8040-218	
D75/25	8042-218	
D34	8012-021	6140-01-450-0141
D34/78	8014-045	6140-01-441-4272
D27F	8037-127	6140-01-600-5785
D31T	8050-160	6140-01-457-5469
D31A	8051-160	6140-01-502-4973
34M	8006-006	6140-01-441-4280, 6140-01-526-2605
D34M	8016-103	6140-01-475-9355
D27M	8027-127	6140-01-589-0622
D31M	8052-161	6140-01-502-4405
H6	7048-148	
H7	7094-197	

Disclaimer

Clarios cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.